

VDP-3 Video Doorphone

Stay Alert to
Protect Your Premises



HD Camera



PIR Motion
Detection



Ultra-Slim
Design




Two-Way
Voice

VDP-3 is an AC-powered video door phone that is designed for you to view and speak with the visitor at the door with a smartphone from anywhere. With a built-in 1080p high resolution camera and night vision technology, this video door phone gives you a clear and wide view, day and night. VDP-3 also has built-in motion sensor to capture alarm videos when irregular motion or presence has been detected.

With its ultra-slim design, small size and multiple color options, VDP-3 can easily match your front door and fit on the door frame. VDP-3 video door phone can also expand its possibilities for home automation applications and security purposes. Remotely unlock the digital door lock, or turning on the hallway lighting and lighting to deter an intruder attempt. With VDP-3, you are always home.



• view and speak with the visitor whenever, wherever you are



• alarm videos when irregular presence has been detected



VDP-3 Video Doorphone

Features

- Built-in motion sensor to detect irregular movements or presence
- Exceptional image quality at 1920 x 1080p
- Built-in IR LED(s) for nighttime monitoring
- HD camera lens covers wide angle of up to 174° degree
- The built-in speaker and microphone provides two-way voice
- IR Motion Detection Range: 5m at 105°degrees*
- Smaller, slim design to easily fit door frame
- Replace existing doorbell without requiring special tools
- Ideal for residential and commercial premises
- Multiple color options: White, Silver

Specifications

Camera	
Image Sensor	2 megapixel Progressive Scan CMOS
Field of View	174° (Diagonal); 148° (Horizontal); 79° (Vertical)
Resolution (max)	1920 x 1080p
Camera Lens	F2.0 fixed focus
Video Compression	H.264
Max Frame Rate	1920 x 1080p at 15 fps
PIR Motion Sensor	
Range	5m
Horizontal Angle	105° degrees
Installation Height	At least 1.3m ~ 1.4m
Mechanical	
WiFi Interface	IEEE 802.11 b/g/n (2.4GHz)
Audio	Two-way voice
Night Vision	IR LED
Power Source	12V DC or 24V AC
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	118mm x 49mm x 32mm